

DLQ LIQUID APPLICATOR

MODELS

- 21' BAR - SINGLE FOLD
- 27' BAR - SINGLE FOLD
- 32' BAR - SINGLE FOLD
- 35' BAR - SINGLE FOLD
- 35' BAR - HYDRAULIC DOUBLE FOLD
- 42' BAR - HYDRAULIC DOUBLE FOLD



FEATURES

- 20" Coulters injection, Coulters/Knife Combo, & knife only are available for fertilizer application
- The spring-loaded ground driven pump is mounted on the front bar for better visibility and automatically stops when toolbar is lifted for turnaround
- Adjustable dual clevis and 10,000 lb. drop foot jack
- Front hose stand keeps hoses away from tractor hitch
- High clearance 42" Radial lug tires with 8-bolt hubs gives you maximum crop clearance.

SPECIFICATIONS

WORKING WIDTH: 21'6" - 27'6" - 32'6" - 42'6"
TOOLBAR & MAINFRAME: 4"X6" RECTANGULAR TUBE
TIRE SIZE: 12.4/42 - 8-BOLT WHEEL
TANK SIZES: 500 GAL., 750 GAL., & 1000 GAL.

The DLQ Series Liquid Applicator is built tough for the most rugged terrain. The 4"X6" tubular main frame and the 4"X6" front mount toolbar gives you the strength and visibility you need in today's environment.

This unit features the versatility of handling a 21' to 42' toolbar and 15"-36" row spacing. The ground driven pump and drive system include a 15' bar lug shur grip tire and stainless steel drive train.

Optional hydraulic pump or single/twin piston pump gives you a large range of application rates. The coulters injection equipped with straight stream nozzle applies the fertilizer where needed.



SIMPLE. DURABLE. AMERICAN

DLQHD LIQUID APPLICATOR

MODELS

27' BAR - SINGLE FOLD
32' BAR - SINGLE FOLD
35' BAR - SINGLE FOLD
35' BAR - HYDRAULIC DOUBLE FOLD
42' BAR - HYDRAULIC DOUBLE FOLD
60' BAR - TRI FOLD

The DLQHD Series Liquid Applicator features heavy duty construction to handle the most extreme of conditions. Our front mount toolbar is made of 4"x6" tubing giving the strength and visibility you need. Models come in various row spacing and range up to 60' wide.



FEATURES

Removable spacer to adjust wing flex

Coulter Injection, Coulter/Knife Combo, & Knife only are available for fertilizer application

The spring-loaded ground driven pump is mounted on the front bar for better visibility and is also available with a hydraulic driven pump

Adjustable dual clevis and 10,000 lb. drop foot jack

Front hose stand keeps hoses away from tractor hitch

High 46" lug tires with heavy 10-bolt hubs gives you maximum clearance

SPECIFICATIONS

WORKING WIDTH: 27'6"-32'6"-35'6"-42'6" & 60'6"

TOOLBAR: 4"X 6" RECTANGULAR TUBE

TIRE SIZE: 14.9/46 - 10-BOLT WHEEL

TANK SIZES: 1000 GAL., 1250 GAL., 1600 GAL. & 2000 GAL.

Dalton
AG PRODUCTS



602 E. Van Buren
Lenox, Iowa 50851

www.DaltonAg.com

office@daltonag.com

800.342.7498

100% EMPLOYEE OWNED