

MOBILITY DRY FERTILIZER SPREADER

MODELS: 600, & 800



DUAL GEARBOX DRIVEN SPINNERS
WITH ADJUSTMENT BOLT ON FINS



HIGH CLEARANCE PTO SHAFT
VIRTUALLY EMLIMINATES PTO DAMAGE



WALKING BEAM SUSPENSION

STAINLESS STEEL

M·BILITY
BY DALTON AG

SIMPLE. DURABLE. AMERICAN.

SPECIFICATIONS

	600 - 6 TON	800 - 8 TON
OVERALL LENGTH	205"	220"
OVERALL HEIGHT	92"	103"
OVERALL WIDTH	96"	97"
HOPPER CAPACITY	200 CU. FT.	270 CU. FT.
WEIGHT	3100 LBS	4000 LBS
TIRES	16.5L x 16.1	19L x 16.1 x 12 Ply Tires
SPREAD PATTERN	40' - 50' - 60'	40' - 50' - 60'

FEATURES

2 SPEED CONVEYOR DRIVE
DEFLECTOR SHIELD
FITTED VINYL TARP
STANDARD 540 RPM PTO
5000 LB. JACK
SAFETY CHAINS
STAINLESS STEEL BOX, LEGS,
& APRON

OPTIONS

VARIABLE RATE
AGRI-TARP ROLL COVER
2-WHEEL SURGE BREAKS
HYDRAULIC ON/OFF FOR
CONVEYOR
540 RPM OR 1000 RPM PTO
HONDA 8HP MOTOR WITH
ELECTRIC START POWERED
SPINNERS
TRACTOR HYDRAULIC POWERED
SPINNERS