

LIME & FERTILIZER COMBO SPREADER

C Series

MODELS

C220, C300, C400



- Three models with up to 12 ton capacity
- Handles dry fertilizer & lime with ease
- Conveyor & spinners driven by tractor hydraulic system - perfect for VRT applications
- Up to 80' spread pattern for fertilizer
- Stainless steel painted hopper resists corrosion
- Heavy duty 8x2 tubular steel frame
- Ultra-durable powder coat paint for protection against the elements

M·BILITY
BY DALTON AG

SIMPLE. DURABLE. AMERICAN.

LIME & FERTILIZER COMBO SPREADER

C Series

FEATURES	C220	C300	C400
Capacity (volume)	220 Cu. Ft.	300 Cu. Ft.	400 Cu. Ft.
Capacity (weight)	10 tons	12 tons	12 tons
Overall length	234"	234"	277"
Overall width	102"	146"	154.5"
Overall height	99"	125"	125"
Hopper length	120"	120"	164"
Hopper width	93"	102"	102"
Construction - hopper	409 SS	409 SS	409 SS
Construction - frame	8x2 rect. Tube	8x2 rect. Tube	8x2 rect. Tube
Metering gate	Adjustable	Adjustable	Adjustable
Axle(s)	Tandem	Single	Single
Wheels	22.5x13.5	30.5x28	25x36
Tires	Used 425/65R 22.5	850/50R30.5	66x4300R25
Braking system	N/A	N/A	N/A
Conveyor	20" SS Mesh	20" SS Mesh	20" SS Mesh
Conveyor drive	Hydraulic	Hydraulic	Hydraulic
Conveyor rate	Variable	Variable	Variable
Spinners	24"	24"	24"
Spinner drive	Hydraulic	Hydraulic	Hydraulic
Spread coverage	80' Fertilizer	80' Fertilizer	80' Fertilizer
Control system	Raven	Raven	Raven
Bull Pull Hitch	Optional	Standard	Standard
Jack	7,000 lbs.	7,000 lbs.	7,000 lbs.
Tractor hydraulic system req.	28 GPM	28 GPM	28 GPM
Lighting	Optional	Optional	Optional
Scale system	N/A	Optional	Optional
Roll Tarp	Optional	Standard	Standard
Standard colors	White	White	White



Heavy duty direct-drive planetary motor eliminates the need for chains, sprockets, belts and pulleys in conveyor driveline.



Direct hook-up to tractor hydraulic system eliminates PTO drive and oil pump/reservoir, and facilitates accurate VRT fertilizer application.



Twin 24" spinners produce a consistent spread pattern up to 80' using dry fertilizer.